

1/3 less installed cost, on average, than our commercial model

Arm attaches to the door or frame

1/2 of the weight of our commercial unit

Less than 1/2 the size of our commercial unit

Available for door mount application with 3-1/2" clearance required behind door or jamb mount on push side of door

Above models totally convertible in field in less than 15 minutes

**POWER
ACCESS**



NEW RESIDENTIAL DOOR OPENER

TECHNICAL DATA

| | |
|------------------------|--|
| Model | 2300 |
| Application | Residential Side Hinged Doors |
| Operation | Unit opens & closes door. Door can also be used manually |
| Mounting | Door mount on pull side (needs 3 ¹ / ₂ " back clearance) - 3" above top of door needed for arm hub Jamb mount on top of push side. Avoid out swinging exterior door |
| Cycle Time | 7 - 8 seconds to open 7 - 8 seconds to close |
| Timed Hold Open | 0 - 30 seconds |
| Activation | Radio 300 (MHz) or wired controls |
| Dimensions | 12 ³ / ₄ " W x 6" H x 3 ¹ / ₂ " D |
| Weight | 10 lbs |
| Electrical | 115 - 1 - 60 (9 - foot power cord) |
| Cover | Gray ABS Plastic |

FEATURES

Designed for retrofitting to most existing residential doors

Built-in radio receiver for a variety of radio controls for remote signal (a transmitter can be chair mounted)

Interfaces with electric strike (lock), ECU controls, sip and puff and others

Unique friction clutch arm provides slippage for safety

One unit fits four configurations – door mount or jamb mount as well as right hand or left hand

Built-in transformer capacity for a 24-vdc electric strike

Very cost effective and simple to install

U.S. Pat. 6,634,140 B1

After 25 years of selling door openers for the accessibility market, Power Access Corporation has released a new lower cost, lighter weight, slim line Model 2300 door opener designed for the home. One unit works for a door mount application on the pull side of the door or a jamb mount application on the push side of the door. Field changing in mere minutes from mode-to-mode or hand-to-hand can be done. The door arm attaches to the door or jamb as the application requires. A unique friction clutch arm and a special gear motor permit safe door operation in both the automatic mode and manual mode.

**Cost
Effective**

**Easy
Installation**



Power Access Corporation

P. O. Box 1050, New Hartford, CT 06057-0980

800-344-0088

www.power-access.com • slsinfo@power-access.com