



MODEL 4300 COMMERCIAL DOOR OPENER

The Model 4300 door opener is designed for use in commercial settings where accessible entry is desired. Rather than attaching to the door or jamb, the arm of the Model 4300 opener has a wheel on the end that rolls the door open.

The passive design leads most foot traffic to open the door manually. This reduces wear-and-tear to a minimum over time, requiring very little maintenance throughout the opener's lifetime (decades)!

MOUNT AND HAND OPTIONS

Jamb Mount: Pushes Door Open



- Unit mounted to jamb and arm pushes door open
- Jamb mount unit requires 5½" clearance above door

FEATURES



Multiple configurations available for standard & unique commercial applications: for example, all glass, extra tall & deep-inset doors



Opener easily interfaces with a variety of controls, including security systems already in place



Built-in safety feature times out & resets unit if obstruction detected on open cycle

BENEFITS



Cost-effective AND durable with very little maintenance needed



Easy to install with step-by-step, illustrated installation guides



Passive design allows for manual door operation without added back-pressure or wear-and-tear



Manufacturer-provided 10-Year Major Component Warranty

TECHNICAL INFO



115VAC, 60Hz (9' or 20' power cord)



Activation: Radio 300 MHz or wired controls



Cycle Time: 7-9 seconds to open; 7-9 seconds to close



Timed Hold Open: 0-30 seconds (optional PTO/PTC)



Weight: 19 lbs
Dimensions: 18 ½"W x 8 ½"H x 7"D

CONTROL OPTIONS

4458SQV
Vestibule
Dual Plate



4494SQ 2¾"
Jamb Switch

4496SR 6"
Round



4499SFA No
Touch Motion-
Activated



4495SQ 4½"
Square



4437S
4-Digit
Keypad
Coded
Entry